



HIGH PERFORMANCE ECO-FABRIC FOR VERTICAL SURFACES

Wallcoverings • Panel Systems • Partitions

Treated with Stain Guard. Stain Guard’s soil and stain resistance adds years to the life of a fabric. It dramatically cuts on-site maintenance and replacement costs, making every installation a better investment investment for your customers.

ECHO SPECIFICATIONS

CONTENT

- 65% polyester
- 35% olefin

35% RECYCLED CONTENT

- 35% post-industrial

BACKING

acrylic latex

FINISH

Stain Guard

WEIGHT

14 oz.

WIDTH

54"

ROLL SIZE

50 yards

FLAMMABILITY

Class A / ASTM E-84
Passes: UBC 8-2
FS: 20 SD: 50
Passes: Cal 117
Passes: Vertical Burn

ABRASION RESISTANCE

(ASTM D-4157-02)
36,000 double rubs

COLOR FASTNESS TO LIGHT

(AATCC-16A)
exceeds Class 4.0 / 40 hrs.

ENVIRONMENTAL

does not contain:

- pvc
- chlorene
- plasticizers
- heavy metals
- formaldehyde
- ozone depleting substances
- volatile organic chemicals (voc's)

conserving natural resources:

- diverts waste from landfills
- offsets the need to refine new crude oil
- requires less energy to produce