

## HIGH PERFORMANCE ECO-FABRIC FOR VERTICAL SURFACES Wallcoverings • Panel Systems • Partitions

reated with Stain Guard. Stain Guard's soil and stain resistance adds years to the life of a fabric. It dramatically cuts on-site maintenance and replacement costs, making every installation a better investment investment for your customers.

# SOUND SPECIFICATIONS

CONTENT BACKING FINISH WEIGHT WIDTH ROLL SIZE

65% polyester acrylic latex Stain Guard 14 oz. 54" 50 yards

· 35% olefin

### **35% RECYCLED CONTENT**

· 35% post-industrial

#### **FLAMMABILITY**

Class A / ASTM E-84 Passes: UBC 8-2 FS: 20 SD: 50 Passes: Cal 117 Passes: Vertical Burn

#### **ABRASION RESISTANCE**

(ASTM D-4157-02) 36,000 double rubs

#### **COLOR FASTNESS TO LIGHT**

(AATCC-16A) exceeds Class 4.0 / 40 hrs.

#### **ENVIRONMENTAL**

#### does not contain:

- · pvc
- · chlorene
- · plasticizers
- · heavy metals
- · formaldehyde
- · ozone depleting substances
- · volatile organic chemicals (voc's)

#### conserving natural resources:

- · diverts waste from landfills
- · offsets the need to refine new crude oil
- · requires less energy to produce

<sup>&</sup>lt;sup>©</sup> Hytex Industries, Inc. 2017 All rights reserved