

-OEM- New Millennium

PHYSICAL SPECIFICATIONS

sofSuede

12 oz.
ABRASION up to 30,000
MINIMUM CYCLES (cotton duck)

- Roll Size: 50 lineal yards
- Fabric Width: 57 ” untrimmed
- Finish: Protected by **Teflon**[®] fabric protector system by Dupont
- Backing: Acrylic latex with mildew inhibitor
- Composition: 100% Polyester Microtextile

VAPOR PERMEABILITY

ASTM E-96, PRODCEDURE B: 114.6 US perms

FINISH

Treated with Teflon [®] fabric protection system by Dupont. Teflon’s soil and stain resistance adds years to the life of a fabric. It drastically cuts on-site maintenance and replacement costs, making every installation a better investment for your customers.

FLAMMABILITY

TUNNEL TEST: Class A 25-60-0 (per NFPA 255. ASTM E-84... tested over ½” type X gypsum board)	
--	--

CORNER BURN: Passes	CIGRETTE IGNITION: UFAC CLASS I
---------------------	---------------------------------

PERFORMANCE

CROCKING: Class 4 (dry), Class 3-4 (wet)	ABRASION RESISTENCE: Up to 30,000 minimum cycles (cotton duck)
--	--

TEAR STRENGTH: (grab) Warp – 70 lbs. Fill – 125 lbs.
--

ANTIMICROBIAL

sofSuede will not mildew, rot, or support the growth of bacteria and is non-allergenic.

MAINTENANCE

Fabric is easy to clean. Depending upon the extent of soilage, use traditional cleaning methods, i.e. washing, wiping, vacuuming. Because liquid spills usually “bead up” on the surface, often all that is needed is quick action with a dry cloth to absorb the liquid.

