

WHISPERTEX

ENVIRONMENTAL SOUND CONTROL FABRICS

Vertical Surfaces • Ceiling Systems • Acoustical Panels

A dimensional fabric which offers excellent acoustical properties, unmatched fade resistance, and a fire/smoke retardant Class A rating. WhisperTex is lightweight, inexpensive, and as easy to install as conventional wallcoverings. It is moisture resistant, mildew, rot, and bacteria resistant, and is non-allergenic. With a commitment to the environment, we manufacture WhisperTex using post-consumer recycled materials and it is fully 100% recyclable.

SPECIFICATIONS

CONTENT FOSSFIBRE® 100% Solution dyed polyester staple fiber	BACKING Radiant fusion	WEIGHT 13 ounces/lineal yard	WIDTH 54"	ROLL SIZE 50 yds.	FLAMMABILITY Passes UBC 8-2/ NFPA 265 Class A / ASTM E-84
--	-------------------------------------	--	---------------------	-----------------------------	--

WhisperTex has been tested for toxicity in accordance with the Pittsburgh Protocol and is no more toxic than wood (LA₅₀ method). New York City MEA Registration #276-90M.

THICKNESS

Coppersmith	.060" (+/- .015")
Plissé	.080"

TEST RESULTS

ASTM E-84 Tunnel Test	Flame Spread Rate 15	Fuel Contributed 15	Smoke Developed 20
--------------------------	-------------------------	------------------------	-----------------------

NOTE: The numerical flame spread rating and other test results referenced herein are not intended to reflect hazards presented by this or any other material under actual fire conditions.

NRC: (ASTM C-423) .60 over acoustical board .05 over gypsum board	MOISTURE REGAIN (ASTM D-2654) .03%	COLOR FASTNESS TO CROCKING (AATCC - 8) Dry - Excellent, Wet - Excellent
COLOR FASTNESS TO LIGHT (AATCC - 16A) 100 hours	ABRASION RESISTANCE (ASTM D - 3597 MOD) Voluntary Prod. TS198 Full Commercial Serviceability	

Installation and maintenance instructions are enclosed with every WhisperTex shipment and should be carefully read prior to installation. For best results, it is recommended that a qualified textile wallcovering installer be employed.