

DOUPPIONI

HIGH PERFORMANCE WOVENS

Wallcoverings • Panels • Exhibits • Partitions

This woven fabric resembles all the attributes of handcrafted silk. The low-luster yarn is used along with a beautiful slub to make this design a sourcing staple.

SPECIFICATIONS

WIDTH:	54"	BACKING:	Acrylic Latex
TOTAL WEIGHT:	13 oz. per linear yard	INSTALLATION:	Non-Reversible / Random Match
FINISH:	StainGuard	CONTENT:	100% Polyester

PERFORMANCE

FLAMMABILITY:	Passes ASTM E-84 Class A Tested in Accordance with CAN/ULC-S102 Tested in Accordance with (EN13501): B-s1,d0 rating
COLORFASTNESS TO LIGHT:	(AATCC Method 16): Class 4 (40 hours)
ABRASION RESISTANCE:	(ASTM D4157) Exceeds 30,000 Wyzenbeek Double Rubs

QUALITY STANDARDS

ENVIRONMENTAL:	Created with No PVC, No Heavy Metals or Formaldehyde, No ODS's, No Phthalates, No VOC's
CLEANING CODE:	WS & BC – Water/Solvent & Bleach Cleanable

INSTALLATION

Customs available upon request. Color & Texture May Vary Slightly Due to the Reflective Quality of the Yarn. Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation. For best results, it is recommended that a qualified textile wallcovering installer be employed.

WARRANTY

5-year limited warranty against manufacturing defects.

USAGE AREAS

HEALTH CARE

- Retirement Facilities
- Nursing Homes
- Hospitals
- Nursing Stations

HOSPITALITY

- Ball Rooms
- Conference Rooms
- Meeting Rooms

DESIGNERS

- Commercial Interiors Market

ENTERTAINMENT

- Theatres
- Recreational Centers

CORPORATE

- Executive Conference Rooms
- General Offices

INSTITUTIONAL

- Schools (Auditorium)
- Government & Mass Trans. Buildings
- Day Care Center