



Coppersmith

ENVIRONMENTAL SOUND CONTROL FABRICS

Vertical Surfaces • Ceiling Systems • Acoustical Panels

A dimensional fabric which offers excellent acoustical properties, unmatched fade resistance, and a fire/smoke retardant Class A rating. Coppersmith is lightweight, inexpensive, and as easy to install as conventional wallcoverings. It is moisture resistant, mildew, rot, and bacteria resistant, and is non-allergenic. With a commitment to the environment, we manufacture WhisperTex using post-consumer recycled materials and it is fully 100% recyclable.

SPECIFICATIONS

<u>CONTENT</u> eco-fi® Polyester Fiber 100% post-consumer recycled plastic bottles	<u>BACKING</u> Radiant Fusion	<u>WEIGHT</u> 13 ounces/lineal yard	<u>WIDTH</u> 54"	<u>ROLL SIZE</u> 50 yds.	<u>FLAMMABILITY</u> Passes UBC 8-2/ NFPA 265 Class A / ASTM E-84
---	-------------------------------------	--	---------------------	-----------------------------	--

Wallcovering • Acoustical Panels • Tack Boards • Ceiling Tiles • Office Partitions

THICKNESS

Coppersmith .060" (+/- .015")

TEST RESULTS

ASTM E-84 Tunnel Test	Flame Spread Rate 15	Fuel Contributed 15	Smoke Developed 20
<p>NOTE: The numerical flame spread rating and other test results referenced herein are not intended to reflect hazards presented by this or any other material under actual fire conditions.</p>			
NRC: (ASTM C-423) .60 over acoustical board .05 over gypsum board	MOISTURE REGAIN (ASTM D-2654) .3%	COLOR FASTNESS TO CROCKING (AATCC - 8) Dry - Excellent, Wet - Excellent	
COLOR FASTNESS TO LIGHT (AATCC - 16A) Class 5 - 40 hours	ABRASION RESISTANCE (ASTM D - 3597 MOD) Voluntary Prod. TS198 Full Commercial Serviceability		
<p>Installation and maintenance instructions are enclosed with every WhisperTex shipment and should be carefully read prior to installation. For best results, it is recommended that a qualified textile wallcovering installer be employed.</p>			

