



## HIGH PERFORMANCE FABRIC FOR VERTICAL SURFACES

Wallcoverings • Panel Systems • Partitions

**T**reated with Teflon® fabric protection system by Dupont. Teflon's soil and stain resistance adds years to the life of a fabric. It dramatically cuts on-site maintenance and replacement costs, making every installation a better investment for your customers.

---

### CAPRI SPECIFICATIONS

**CONTENT**

· 100% polyester

**BACKING**

acrylic latex

**FINISH**

Teflon  
Fabric Protection

**WEIGHT**

13 oz.

**WIDTH**

54"

**ROLL SIZE**

50 yards

**FLAMMABILITY**

Passes: UBC 8-2  
Class A / ASTM E-84  
FS: 25 / SD: 25  
Passes: Cal 117  
Passes: Vertical Burn

**ABRASION RESISTANCE**

(ASTM D-4157-02)  
30,000 double rubs

**COLOR FASTNESS TO LIGHT**

(AATCC-16A )  
exceeds Class 4.0 / 40 hrs.

**ENVIRONMENTAL**

**does not contain:**

- pvc
- chlorene
- plasticizers
- heavy metals
- formaldehyde
- ozone depleting substances
- volatile organic chemicals (voc's)

© Hytex Industries, Inc. 2017 All rights reserved.

Copyright © 2017 DuPont. All rights reserved. The DuPont Oval Logo, DuPont™, The miracles of science™ and all products denoted with ® or ™ are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates.