



# HIGH PERFORMANCE ECO-FABRIC FOR VERTICAL SURFACES

## Wallcoverings • Panel Systems • Partitions

**T**reated with Stain Guard. Stain Guard’s soil and stain resistance adds years to the life of a fabric. It dramatically cuts on-site maintenance and replacement costs, making every installation a better investment investment for your customers.

### ECHO SPECIFICATIONS

**CONTENT**

- 65% polyester
- 35% olefin

**35% RECYCLED CONTENT**

- 35% post-industrial

**BACKING**

acrylic latex

**FINISH**

Stain Guard

**WEIGHT**

14 oz.

**WIDTH**

54"

**ROLL SIZE**

50 yards

**FLAMMABILITY**

Class A / ASTM E-84  
Passes: UBC 8-2  
FS: 20 SD: 50  
Passes: Cal 117  
Passes: Vertical Burn

**ABRASION RESISTANCE**

(ASTM D-4157-02)  
36,000 double rubs

**COLOR FASTNESS TO LIGHT**

(AATCC-16A)  
exceeds Class 4.0 / 40 hrs.

**ENVIRONMENTAL**

**does not contain:**

- pvc
- chlorene
- plasticizers
- heavy metals
- formaldehyde
- ozone depleting substances
- volatile organic chemicals (voc’s)

**conserving natural resources:**

- diverts waste from landfills
- offsets the need to refine new crude oil
- requires less energy to produce