

BACKING

acrylic latex

HIGH PERFORMANCE ECO-FABRIC FOR VERTICAL SURFACES

Wallcoverings • Panel Systems • Partitions

tilizing a combination of pre-consumer and post-consumer recycled polyester to create unique performance yarns, Hytex Industries introduces our newest collection of vertical surface textiles for the commercial market.

WEIGHT

PEBBLE

SPECIFICATIONS

CryptonWall[®] 'Green' 19 oz.

|--|

54"

ROLL SIZE

50 yards

88% polyester
12% olefin

CONTENT

olemn

69% RECYCLED CONTENT

· 20% post-consumer (polyester)

· 37% post-industrial (polyester)

· 12% post-industrial (olefin)

FLAMMABILITY Class A / ASTM E-84

Passes: UBC 8-2 FS: 20 / SD: 50 Passes: Cal 117 Passes: Vertical Burn

ABRASION RESISTANCE

FINISH

Soil & Stain

Repellant

(ASTM D-4157-02) 100,000 double rubs

COLOR FASTNESS TO LIGHT

(AATCC-16A) Class 5.0 / 40 hrs.

ENVIRONMENTAL

does not contain:

- · pvc
- · chlorene
- · plasticizers
- · heavy metals
- · formaldehyde
- · ozone depleting substances
- · volatile organic chemicals (voc's)

conserving natural resources:

- · diverts waste from landfills
- · offsets the need to refine new crude oil
- · requires less energy to produce

Greenguard Gold Certified

- · Number 23850-410
- · formerly Children & Schools Gold Certified
- · meets Calif 1350 High Performance Schools



^o Hytex Industries, Inc. 2017 All rights reserved.

©2017 CRYPTON, Inc. CRYPTON and the planet logo are registered trademarks of CRYPTON, Inc. U.S. patent 5,565,265 and other U.S. and global patents issued and pending.

REPREVE is a registered trademark of Unifi, Inc.