

# Plisse

## ENVIRONMENTAL SOUND CONTROL FABRICS

Vertical Surfaces • Ceiling Systems • Acoustical Panels

**A** dimensional fabric which offers excellent acoustical properties, unmatched fade resistance, and a fire/smoke retardant Class A rating. Plisse is lightweight, inexpensive, and as easy to install as conventional wallcoverings. It is moisture resistant, mildew, rot, and bacteria resistant, and is non-allergenic. With a commitment to the environment, we manufacture WhisperTex using post-consumer recycled materials and it is fully 100% recyclable.

### SPECIFICATIONS

<u>CONTENT</u> eco-fi® Polyester Fiber 100% post-consumer recycled plastic bottles	<u>BACKING</u> Radiant Fusion	<u>WEIGHT</u> 13 ounces/lineal yard	<u>WIDTH</u> 54"	<u>ROLL SIZE</u> 50 yds.	<u>FLAMMABILITY</u> Passes UBC 8-2/ NFPA 265 Class A / ASTM E-84
--	-------------------------------------	--	---------------------	-----------------------------	--

*Wallcovering • Acoustical Panels • Tack Boards • Ceiling Tiles • Office Partitions*

### THICKNESS

Plissé .080" (+/- .015")

### TEST RESULTS

ASTM E-84 Tunnel Test	Flame Spread Rate 15	Fuel Contributed 15	Smoke Developed 20
NOTE: The numerical flame spread rating and other test results referenced herein are not intended to reflect hazards presented by this or any other material under actual fire conditions.			
NRC: (ASTM C-423) .60 over acoustical board .05 over gypsum board	MOISTURE REGAIN (ASTM D-2654) .3%	COLOR FASTNESS TO CROCKING (AATCC - 8) Dry - Excellent, Wet - Excellent	
COLOR FASTNESS TO LIGHT (AATCC - 16A) Class 5 - 40 hours	ABRASION RESISTANCE (ASTM D - 3597 MOD) Voluntary Prod. TS198 Full Commercial Serviceability		
Installation and maintenance instructions are enclosed with every WhisperTex shipment and should be carefully read prior to installation. For best results, it is recommended that a qualified textile wallcovering installer be employed.			

