



HIGH PERFORMANCE ECO-FABRIC FOR VERTICAL SURFACES

Wallcoverings • Panel Systems • Partitions

Treated with Teflon® fabric protection by Dupont. Teflon's soil and stain resistance adds years to the life of a fabric. It dramatically cuts on-site maintenance and replacement costs, making every installation a better investment for your customers.

CONTOUR SPECIFICATIONS

<u>CONTENT</u>	<u>BACKING</u>	<u>FINISH</u>	<u>WEIGHT</u>	<u>WIDTH</u>	<u>ROLL SIZE</u>
<ul style="list-style-type: none">· 75% polyester· 25% olefin	acrylic latex	Teflon Fabric Protection	13 oz.	54"	50 yards
<u>25% RECYCLED CONTENT</u>					
<ul style="list-style-type: none">· 25% post-industrial					

FLAMMABILITY

Class A / ASTM E-84
Passes: UBC 8-2
FS: 20 / SD: 50
Passes: Cal 117
Passes: Vertical Burn

ABRASION RESISTANCE

(ASTM D-4157-02)
30,000 double rubs

COLOR FASTNESS TO LIGHT

(AATCC-16A)
exceeds Class 4.0 / 40 hrs.

ENVIRONMENTAL

does not contain:

- pvc
- chlorene
- plasticizers
- heavy metals
- formaldehyde
- ozone depleting substances
- volatile organic chemicals (voc's)

conserving natural resources:

- diverts waste from landfills
- offsets the need to refine new crude oil
- requires less energy to produce

© Hytex Industries, Inc. 2017 All rights reserved.

Copyright © 2017 DuPont. All rights reserved. The DuPont Oval Logo, DuPont™, The miracles of science™ and all products denoted with ® or ™ are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates.