

HIGH PERFORMANCE ECO-FABRIC FOR VERTICAL SURFACES Wallcoverings • Panel Systems • Partitions

reated with Stain Guard. Stain Guard's soil and stain resistance adds years to the life of a fabric. It dramatically cuts on-site maintenance and replacement costs, making every installation a better investment investment for your customers.

JAZZ SPECIFICATIONS

<u>CONTENT</u>	BACKING	<u>FINISH</u>	<u>WEIGHT</u>	<u>WIDTH</u>	ROLL SIZE
· 96% polyester	acrylic latex	Stain Guard	13 oz.	54"	50 yards

· 4% metalized polyester yarn

RECYCLED

· up to 96% post-consumer content (varies by color, minimum 62%)

FLAMMABILITY

Class A / ASTM E-84 Passes: UBC 8-2 FS: 25 / SD: 25 Passes: Cal 117 Passes: Vertical Burn

ABRASION RESISTANCE

(ASTM D-4157-02) 51,000 double rubs

COLOR FASTNESS TO LIGHT

(AATCC-16A) exceeds Class 4.0 / 40 hrs.

ENVIRONMENTAL

does not contain:

- · pvc
- · chlorene
- · plasticizers
- $\cdot \text{ heavy metals} \\$
- · formaldehyde
- · ozone depleting substances
- · volatile organic chemicals (voc's)

conserving natural resources:

- · diverts waste from landfills
- \cdot offsets the need to refine new crude oil
- · requires less energy to produce

[©] Hytex Industries, Inc. 2017 All rights reserved.