

HIGH PERFORMANCE FABRIC FOR VERTICAL SURFACES

Wallcoverings • Panel Systems • Partitions

Treated with Stainguard. Stainguard's soil and stain resistance adds years to the life of a fabric. It dramatically cuts on-site maintenance and replacement costs, making every installation a better investment for your customers.

CONTOUR SPECIFICATIONS

CONTENT

- 75% polyester
- 25% olefin

25% RECYCLED CONTENT

- 25% post-industrial

BACKING

acrylic latex

FINISH

Stainguard

WEIGHT

13 oz.

WIDTH

54"

ROLL SIZE

50 yards

FLAMMABILITY

Class A / ASTM E-84
Passes: UBC 8-2
FS: 20 / SD: 50
Passes: Cal 117
Passes: Vertical Burn

ABRASION RESISTANCE

(ASTM D-4157-02)
30,000 double rubs

COLOR FASTNESS TO LIGHT

(AATCC-16A)
exceeds Class 4.0 / 40 hrs.

ENVIRONMENTAL

does not contain:

- pvc
- chlorene
- plasticizers
- heavy metals
- formaldehyde
- ozone depleting substances
- volatile organic chemicals (voc's)

conserving natural resources:

- diverts waste from landfills
- offsets the need to refine new crude oil
- requires less energy to produce

© Hytex Industries, Inc. 2017 All rights reserved.

Copyright © 2017 DuPont. All rights reserved. The DuPont Oval Logo, DuPont™, The miracles of science™ and all products denoted with © or ™ are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates.