HIGH PERFORMANCE FABRIC FOR VERTICAL SURFACES

Wallcoverings • Panel Systems • Partitions

Treated with Stainguard. Stainguard's soil and stain resistance adds years to the life of a fabric. It dramatically cuts on-site maintenance and replacement costs, making every installation a better investment for your customers.

SONORA SPECIFICATIONS

 CONTENT
 BACKING
 FINISH
 WEIGHT
 WIDTH
 ROLL SIZE

 ⋅ 53% polyester
 acrylic latex
 Stainguard
 14 oz.
 54"
 50 yards

· 47% olefin

47% RECYCLED CONTENT

· 47% post-industrial

FLAMMABILITY

Class A / ASTM E-84 Passes: UBC 8-2 FS: 20 / SD: 50 Passes: Cal 117 Passes: Vertical Burn

ABRASION RESISTANCE

(ASTM D-4157-02) 51,000 double rubs

COLOR FASTNESS TO LIGHT

(AATCC-16A) exceeds Class 4.0 / 40 hrs.

ENVIRONMENTAL

does not contain:

- pvc
- · chlorene
- plasticizers
- · heavy metals
- · formaldehyde
- · ozone depleting substances
- · volatile organic chemicals (voc's)

conserving natural resources:

- · diverts waste from landfills
- · offsets the need to refine new crude oil
- · requires less energy to produce

[©] Hytex Industries, Inc. 2017 All rights reserved.