

HIGH PERFORMANCE ECO-FABRIC FOR VERTICAL SURFACES Wallcoverings • Panel Systems • Partitions

tilizing a combination of pre-consumer and post-consumer recycled polyester to create unique performance yarns, Hytex Industries introduces our newest collection of vertical surface textiles for the commercial market.

AVALON SPECIFICATIONS

CONTENT BACKING FINISH WEIGHT WIDTH ROLL SIZE

67% polyester acrylic latex CryptonWall® 'Green' 18 oz. 54" 50 yards

33% olefin Soil & Stain

Repellant

43% RECYCLED CONTENT

- · 10% post-consumer (polyester)
- · 33% post-industrial (olefin)

FLAMMABILITY

Passes: NFPA 265 Class A / ASTM E-84 FS: 20 / SD: 50 Passes: Cal 117 Passes: Vertical Burn

ABRASION RESISTANCE

(ASTM D-4157-02) 100,000 double rubs

COLOR FASTNESS TO LIGHT

(AATCC-16A) Class 5.0 / 40 hrs.

ENVIRONMENTAL

does not contain:

- · pvc
- · chlorene
- · plasticizers
- · heavy metals
- · formaldehyde
- · ozone depleting substances
- · volatile organic chemicals (voc's)

conserving natural resources:

- · diverts waste from landfills
- · offsets the need to refine new crude oil
- · requires less energy to produce

Greenguard Gold Certified

- · Number 23850-410
- · formerly Children & Schools Gold Certified
- · meets Calif 1350 High Performance Schools



 $^{^{\}circ}$ Hytex Industries, Inc. 2017 All rights reserved.