HIGH PERFORMANCE FABRIC FOR VERTICAL SURFACES

Wallcoverings • Panel Systems • Partitions

Treated with Stainguard. Stainguard's soil and stain resistance adds years to the life of a fabric. It dramatically cuts on-site maintenance and replacement costs, making every installation a better investment for your customers.

MING

SPECIFICATIONS

CONTENT BACKING FINISH WEIGHT WIDTH **ROLL SIZE** · 100% polyester acrylic latex Stainguard 13 oz. 54" 50 yards 52% RECYCLED CONTENT

· 52% post-industrial

FLAMMABILITY Class A / ASTM E-84

Passes: UBC 8-2

FS: 25 / SD: 25 Passes: Cal 117 Passes: Vertical Burn

ABRASION RESISTANCE

(ASTM D-4157-02) 51,000 double rubs

COLOR FASTNESS TO LIGHT

(AATCC-16A) exceeds Class 4.0 / 40 hrs.

ENVIRONMENTAL

does not contain:

- pvc
- · chlorene
- · plasticizers
- · heavy metals
- · formaldehyde
- · ozone depleting substances
- · volatile organic chemicals (voc's)

conserving natural resources:

- · diverts waste from landfills
- · offsets the need to refine new crude oil
- · requires less energy to produce

[®] Hytex Industries, Inc. 2017 All rights reserved.