

ZEST

HIGH PERFORMANCE WOVENS

Wallcoverings • Panels • Exhibits • Partitions

This High-Performance wall fabric shifts from the dramatic to the subtle in its reaction to light.

The exciting look offers many application possibilities in a lustrous palette that sparkles.

SPECIFICATIONS

WIDTH:	54"	INSTALLATION:	Non-Reversible / Random Match
TOTAL WEIGHT:	15 oz. per linear yard	CONTENT:	57% Polyester,
FINISH:	Stain Repellent		10% Post-Consumer Recycled Polyester,
BACKING:	Acrylic		33% Olefin

PERFORMANCE

FLAMMABILITY:	Passes ASTM E-84 Class A Tested in Accordance with CAN/ULC-S102 Tested in Accordance with (EN13501): B-s1,d0 rating
COLORFASTNESS TO LIGHT:	(AATCC Method 16): Class 4 (40 hours)
ABRASION RESISTANCE:	(ASTM D4157) Exceeds 100,000 Wyzenbeek Double Rubs

QUALITY STANDARDS

ENVIRONMENTAL:	Created with No PVC, No Heavy Metals or Formaldehyde, No ODS's, No Phthalates, No VOC's
SUSTAINABLE MATERIALS:	Produced Using Recycled Content
CLEANING CODE:	W & BC – Water & Bleach Cleanable
LEED CONTRIBUTION:	Can Contribute Towards LEED Points

INSTALLATION

Color & texture may vary slightly due to the nature of the fiber & structure.

Installation and maintenance instructions are enclosed with every shipment and should be carefully read prior to installation.

For best results, it is recommended that a qualified textile wallcovering installer be employed.

WARRANTY

5-year limited warranty against manufacturing defects.

USAGE AREAS

HEALTH CARE

- Retirement Facilities
- Nursing Homes
- Hospitals
- Nursing Stations

HOSPITALITY

- Ball Rooms
- Conference Rooms
- Meeting Rooms

DESIGNERS

- Commercial Interiors Market

ENTERTAINMENT

- Theatres
- Recreational Centers

CORPORATE

- Executive Conference Rooms
- General Offices

INSTITUTIONAL

- Schools (Auditorium)
- Government & Mass Trans. Buildings
- Day Care Center